

LZT Series Acrylic Flow Meter

Technical Parameters of LZT -G series flow meter

Model	Range			Screw thread	Accuracy
	GPM(Liquid)	LPM(Liquid)	Nm ³ /h(Gas)		
LZT-15G		10-100LPH	0.1-1 0.3-3	1/2"	± 4%
		16-160LPH			
		25-150LPH			
	0.05-0.5	0.2-2	0.6-6 1-10		
	0.1-1	0.5-4	1.6-16 2.5-25		
LZT-20G	0.2-2	1-7	4-40	3/4"	± 4%
	0.3-3	1-11			
	0.5-5	2-18			
	1-10	5-35			
	2-16	10-60			
LZT-25G	2-20	10-70	6-60 10-100	1" B 1-1/2"	± 4%
	3-30	12-120			
	4-40	15-150			
	5-45	20-170			
	4-40	15-150			
LZT-40G	6-60	25-240	100-500	1-1/2"	± 4%
	8-80	30-300			
	10-100	50-350	120-600		
	20-80	80-300	300-850		
	20-100	80-360	300-1000		
LZT-50G	40-120	150-450	100-500	2" 2"	± 4%
	50-150	150-600			
	50-200	200-800	120-600		
	50-300	200-1000	300-850		
	50-400	200-1500	400-1200		
LZT-75G			500-1400	3" 3"	± 4%



LZT-G Pipe flowmeter dimension

Model	Size (mm)		
	A	B	C
LZT-15G	210	180	32
LZT-20G	278	210	45
LZT-25G	265	235	51
LZT-40G	302	230	68
LZT-50G外	380	270	75
LZT-50G内	340	270	75
LZT-75G	400	290	100

Note: For buyer's convenience, we design two constructions for this series of flowmeter, one is circular, and the other one is quadrate, their measure range is same, LZT-G Circular tube type flowmeter, LZT-GF Quadrate tube type flowmeter. The LZT-G series diameter C is the width and height of the LZT-GF series, the same size as the A and B.

The material of LZT -G Series flow meter

Fitting	O-ring
1. ABS	Silicone ring 2. Fluoroplastic rubber 3. Butyl
2. PP	
3. PVC	
4. Brass	
5. Brass chromeplate	
6. SS	

