




HS/HH Series Electro Magnetic Metering (Solenoid) Dosing Pumps - up to 80LPH





- HD Process Electromagnetic metering pump uses a reciprocating electromagnetic push rod drive diaphragm in the pump head, with suction and discharge valving, to achieve the quantitative suction and discharge of liquid.
- The electromagnetic metering pump is a metering pump driven by electromagnet, designed for conveying small flow and low pressure pipeline liquid. It is popular in industry for its simple structure, small energy consumption, accurate measurement and convenient adjustment. Its design principle is “simple and practical”.
- This style of metering pump is widely used in petroleum, chemical industry, power metallurgy, mining, shipbuilding, light industry, agriculture and utilities.

HS&HH Series Electronic Metering Pump



HS Series unit:mm



HH Series unit:mm

Technical Data				
Model	Pressure(Bar)	Flow(L/H)	Speed(Strokes/Min)	Connection Size(Inch)
HS1600	16	0.4	60	3/8" * 1/4"
HS1601	16	0.6	90	3/8" * 1/4"
HS1602	16	0.8	120	3/8" * 1/4"
HS1200	12	0.6	90	3/8" * 1/4"
HS1201	12	0.8	120	3/8" * 1/4"
HS1202	12	1.2	180	3/8" * 1/4"
HS0803	8	3	90	3/8" * 1/4"
HS0804	8	4	120	3/8" * 1/4"
HS0806	8	6	180	3/8" * 1/4"
HS0306	3	5.5	90	3/8" * 1/4"
HS0308	3	7.3	120	3/8" * 1/4"
HS0311	3	11	180	3/8" * 1/4"
HS0211	1.5	11	90	3/8" * 1/4"
HS0215	1.5	14.5	120	3/8" * 1/4"
HS0222	1.5	22	180	3/8" * 1/4"
HH0710	7	10	60	3/8" * 1/4"
HH0715	7	15	90	3/8" * 1/4"
HH0720	7	20	120	3/8" * 1/4"
HH0416	4	16	60	3/8" * 1/4"
HH0424	4	24	90	3/8" * 1/4"
HH0432	4	32	120	3/8" * 1/4"
HH0240	1.5	40	60	DN15/19*26
HH0260	1.5	60	90	DN15/19*26
HH0280	1.5	80	120	DN15/19*26

Liquid Ends Material		
Component	Standard	Optional
Pumphead	PP	/
Diaphragm	PTFE	/
Valve body	PP	/
Valve ball	CERAMICS	/
Valve seat	FPM	PTFE
Valve spring	HASTELLOY	/
Seals	FPM	EPDM