

# Tank equipment - Manways



- Stainless steel construction, AISI 304L or AISI 316L
- Quality European design and manufacture
- Wide range of gasket material options - natural rubber, nitrile, EPDM and viton (food grade certified)

## ▶ A Series - inward opening



**A1**

- P max: 3,8 bar
- Size: 445 x 340mm
- Flat frame, can be bent on request to suit



**A4**

- P max: 3,2 bar
- Size: 440 x 340mm
- 80 x 12mm frame



**A7 Eco**

- P max: 3 bar
- Size: 440 x 310mm
- Horizontal mount



**A8 Eco**

- P max: 3 bar
- Size: 440 x 310mm
- Vertical mount



**A10 Eco**

- P max: 3 bar
- Size: 440 x 310mm
- No hinge




**A15**

- P max: 8 bar
- Size: 520 x 420mm
- 60 x 12mm frame
- Locating lugs, telescopic adjustment, swivel hinge



**A16**

- P max: 8 bar
- Size: 520 x 420mm
- 100 x 12mm frame (150mm avail)
- Locating lugs, telescopic adjustment, swivel hinge



**A21**

- P max: 6 bar
- Size: 520 x 420mm
- 80mm frame height (up to 160mm)
- No hinge



**A29**

- P max: 4 bar
- Size: 560 x 450mm
- 100 x 10mm frame (130mm avail)
- Locating lugs, telescopic adjustment, swivel hinge

## ▶ A Series - outward opening



**A13**

- P max: -1.0/+0.7 bar
- Size: 440 x 310mm
- 80 x 8mm frame



**A25**

- P max: 0,5 bar
- Size: 480 x 380mm
- 80 x 8mm frame



**A28**

- P max: -1.0/+1.0 bar
- Size: 440 x 310mm
- Glass cover for viewing

## ▶ D Series - pressure manways



**D2**

- P max: -1.0/+15 bar
- 150, 200 and 250 mm size
- 100 frame height



**D3**

- P max: -1.0/+6 bar
- Sizes: 300 to 800mm
- Sight glass optional



**D13 - PED Certified**

- P max: up to 10 bar, depending on temperature
- Sizes: 300 to 700mm
- Sight glass optional

# Tank equipment - Manways



- Stainless steel construction, AISI 304L or AISI 316L
- Quality European design and manufacture
- Wide range of gasket material options – natural rubber, nitrile, EPDM and viton (food grade certified)

## ▶ B Series – outward opening



**B1**

- P max: -1.0/+1.0 bar
- 750 x 450mm size in stock
- 600 x 600 and 750 x 750mm sizes on request
- 70 x 8mm frame height



**B2 Eco**

- P max: -1.0/+1.2 bar
- Size: 530 x 410mm
- 60 x 8mm frame
- Other frame heights available
- Vertical mounting



**B6 Eco**

- P max: -1.0/+1.1 bar
- Size: 530 x 410mm
- 60 x 8mm frame
- Other frame heights available
- Horizontal mounting



**B7**

- P max: -1.0/+0.6 bar
- Size: 420 x 310mm
- 60 x 10mm frame

## ▶ D Series – round outward opening



**D8**

- P max: -0.5/+0.2 bar
- Sizes: 200 to 600mm
- 100 frame height
- Swivel hinge



**D9 Eco**

- P max: 0.02 bar
- 150 and 250mm in stock
- 60mm frame height
- Other sizes on request



**D10**

- P max: 0.2 bar
- 200mm size in stock
- 50mm frame height
- Other sizes and frame heights on request



**D14**

- P max: -0.8/+0.3 bar
- Sizes: 500 to 1600mm
- 100 frame height



**D15**

- P max: -0.5/+0.3 bar
- Sizes: 420 to 800 mm
- 100 frame height



**D20**

- P max: -0.5/+0.2 bar
- Sizes: 200 to 1600 mm
- 100 frame height



**D22 Eco**

- P max: -0.3/+0.1 bar
- Sizes: 200 to 600 mm
- 100 frame height